



# Material Safety Data Sheet

MSDS# 15-0288

## Section 1. Chemical Product and Company Identification

<b>Product name</b>	<b>ARQUAD® 12-50</b>	
<b>Material Uses</b>	: Surfactant.	<b>In Case of Emergency</b>
<b>Supplier/ Manufacturer</b>	AKZO NOBEL SURFACE CHEMISTRY LLC 525 West Van Buren Chicago, IL 60607-3823 www.surfactants.akzonobel.com  AKZO NOBEL CHEMICALS LTD. 1 City Centre Drive, Suite 318 Mississauga, Ontario L5B 1M2 Canada	CHEMTREC: 800-424-9300 CANUTEC: 613-996-6666 Medical/Handling: 914-693-6946 Product/Technical: 800-906-9977

## Section 2. Hazards Identification

<b>Physical State</b>	Liquid.
<b>Color</b>	Colorless to light yellow.
<b>Odor</b>	Alcohol like.
<b>Emergency Overview</b>	<p>DANGER!            CAUSES EYE AND SKIN BURNS.            VERY TOXIC TO AQUATIC ORGANISMS.            CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:            RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.            FLAMMABLE LIQUID AND VAPOR.            VAPOR MAY CAUSE FLASH FIRE.            MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED.            CONTAINS MATERIAL WHICH MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS:            GASTROINTESTINAL TRACT.</p> <p>Keep away from heat, sparks and flame. Do not get in eyes, on skin or on clothing. Avoid prolonged contact with eyes, skin, and clothing. Do not ingest. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Avoid contact of spilled material and runoff with soil and surface waterways.</p>
<b>Possible Carcinogenic Effects</b>	<p><b>1-dodecanaminium, n,n,n-trimethyl-, chloride:</b> IARC, NTP, OSHA, ACGIH: Not listed.  <b>Isopropanol:</b> IARC 3; ACGIH NTP OSHA Not listed.  <b>water:</b> IARC, NTP, OSHA, ACGIH: Not listed.  <b>N,N-Dimethyl-1-dodecanamine hydrochloride:</b> IARC, NTP, OSHA, ACGIH: Not listed.  <b>lauryldimethylamine:</b> IARC, NTP, OSHA, ACGIH: Not listed.</p>
<b>Routes of Entry</b>	Absorbed through skin. Dermal contact. Eye contact.

See Toxicological Information (section 11)

## Section 3. Composition/ Information on Ingredients

Name	CAS #	% by Weight
1-dodecanaminium, n,n,n-trimethyl-, chloride	112-00-5	45-55
Isopropanol	67-63-0	35-45
water	7732-18-5	5-15
N,N-Dimethyl-1-dodecanamine hydrochloride	Not Assigned	0.001-2
lauryldimethylamine	112-18-5	0.001-2

Continued on Next Page

---

## Section 4. First Aid Measures

---

<b>Eye Contact</b>	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention immediately.
<b>Skin Contact</b>	In case of contact, immediately flush skin with plenty of water for at least 30 minutes while removing contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
<b>Ingestion</b>	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.
<b>Medical Conditions Aggravated by Overexposure</b>	Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

---

## Section 5. Fire Fighting Measures

---

<b>Flammability of the Product</b>	Flammable.
<b>Auto-ignition Temperature</b>	398°C (748.4°F)
<b>Flash Points</b>	Closed cup: 19°C (66.2°F).
<b>Flammable Limits</b>	The greatest known range is LOWER: 2% UPPER: 12.7% (Isopropanol)
<b>Products of Combustion</b>	These products are carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO, NO <sub>2</sub> ...), halogenated compounds, hydrogen chloride.
<b>Fire Fighting Media and Instructions</b>	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
<b>Protective Clothing (Fire)</b>	Be sure to use an approved/certified respirator or equivalent.
<b>Special Remarks on Fire Hazards</b>	No sparking tools should be used. Take precautionary measures against static discharges.

---

## Section 6. Accidental Release Measures

---

<b>Small Spill and Leak</b>	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. If necessary: <b>Use suitable protective equipment (Section 8).</b>
<b>Large Spill and Leak</b>	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. <b>Use suitable protective equipment (Section 8).</b>

---

## Section 7. Handling and Storage

---

<b>Handling</b>	Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
<b>Storage</b>	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

---

## Section 8. Exposure Controls/ Personal Protection

### Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

### Personal Protection

#### Eyes

Face shield.

#### Body

Full suit.

#### Respiratory

Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.

#### Hands

Gloves.

#### Feet

Boots.

### Protective Clothing (Pictograms)



### Personal Protection in Case of a Large Spill

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

### Ingredient Name

1-dodecanaminium, n,n,n-trimethyl-, chloride  
Isopropanol

### Exposure Limits United States

Not available.

#### ACGIH TLV (United States, 2005). Notes: ACGIH 2003 Adoption Refers to Appendix A -- Carcinogens.

STEL: 400 ppm 15 minute(s). Form: All forms

TWA: 200 ppm 8 hour(s). Form: All forms

#### NIOSH REL (United States, 2001).

STEL: 1225 mg/m<sup>3</sup> 15 minute(s). Form: All forms

STEL: 500 ppm 15 minute(s). Form: All forms

TWA: 980 mg/m<sup>3</sup> 10 hour(s). Form: All forms

TWA: 400 ppm 10 hour(s). Form: All forms

#### OSHA PEL (United States, 1997).

TWA: 980 mg/m<sup>3</sup> 8 hour(s). Form: All forms

TWA: 400 ppm 8 hour(s). Form: All forms

#### OSHA PEL 1989 (United States, 1989).

STEL: 1225 mg/m<sup>3</sup> 15 minute(s). Form: All forms

STEL: 500 ppm 15 minute(s). Form: All forms

TWA: 980 mg/m<sup>3</sup> 8 hour(s). Form: All forms

TWA: 400 ppm 8 hour(s). Form: All forms

water

Not available.

N,N-Dimethyl-1-dodecanamine

Not available.

hydrochloride

lauryldimethylamine

Not available.

## Section 9. Physical and Chemical Properties

### Physical State

Liquid.

### Color

Colorless to light yellow.

### Odor

Alcohol like.

### pH

Basic.

### Boiling/Condensation Point

80°C (176°F)

### Melting/Freezing Point

-10°C (14°F)

### Density

0.892 g/cm<sup>3</sup> (25°C / 77°F)

### Vapor Pressure

5.9 kPa (44 mmHg) (at 20°C)

<b>Vapor Density</b>	2 (Air = 1)
<b>Odor Threshold</b>	The lowest known value is 37 to 600 ppm (Isopropanol)
<b>Evaporation Rate</b>	1.6 compared to Butyl acetate.
<b>Solubility</b>	Easily soluble in hot water, acetone. Soluble in cold water, methanol.
<b>Dispersion Properties</b>	See solubility in water, methanol, acetone.
<b>Physical Chemical Comments</b>	Viscosity = 819SSU @ 38°C.

## Section 10. Stability and Reactivity

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility with Various Substances</b>	Reactive with OXIDIZING AGENTS.
<b>Hazardous Decomposition Products</b>	These products are halogenated compounds, hydrogen chloride.
<b>Hazardous Polymerization</b>	Will not occur.

## Section 11. Toxicological Information

### Toxicity to Animals

Ingredient Name or Product name	Test	Result	Route	Species
1-dodecanaminium, n,n,n-trimethyl-, chloride	LD50	684 mg/kg	Oral	Rat based on data for: (similar material)
	LD50	1600 mg/kg	Dermal	Rabbit based on data for: (similar material)
Isopropanol	LDLo	300 mg/kg	Oral	Mouse
	LD50	5045 mg/kg	Oral	Rat
	LD50	6410 mg/kg	Oral	Rabbit
	LD50	3600 mg/kg	Oral	Mouse
	LD50	12800 mg/kg	Dermal	Rabbit
	LDLo	1537 mg/kg	Oral	Dog
	LDLo	3570 mg/kg	Oral	human
	LDLo	5272 mg/kg	Oral	man
	LC50	12000 ppm (8 hour(s))	Inhalation	Rat
lauryldimethylamine	LC50	16970 ppm (4 hour(s))	Inhalation	Rat
	LD50	1220 mg/kg	Oral	Rat based on data for: (similar material)

### Special Remarks on Toxicity to Animals

**1-dodecanaminium, n,n,n-trimethyl-, chloride:** Similar Material: Acute Oral LD50 (Bobwhite quail) = 565 mg/kg  
 Similar Material: 8-day dietary LC50 (Bobwhite quail) >5000 ppm  
 Similar Material: 8-day dietary LC50 (Mallard ducks) >5000 ppm  
 Similar Material: Hydrolytically stable for 33 days at pH 5, 7 or 9.

### Chronic Effects on Humans

**CARCINOGENIC EFFECTS:** Classified None. by NIOSH [Isopropanol]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Isopropanol]. Classified None. by NIOSH [lauryldimethylamine].

**MUTAGENIC EFFECTS:** Non-mutagenic for bacteria and/or yeast. [Isopropanol].  
 Contains material which causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.  
 Contains material which may cause damage to the following organs: gastrointestinal tract.

### Special Remarks on Chronic Effects on Humans

**1-dodecanaminium, n,n,n-trimethyl-, chloride:** Negative in Cell Transformation study.  
 EC50 (neutral uptake) = 1.0 ug/ml. based on data for: (similar material)  
 EC50 (LOH leakage) = 4.2 ug/ml. based on data for: (similar material)  
 EC50 (SRB protein) = 1.3 ug/ml. based on data for: (similar material)

<b>Acute Effects Skin</b>	Corrosive to the skin. Harmful in contact with skin.
<b>Acute Effects Eyes</b>	Corrosive to the eyes.
<b>Special Remarks on Other Toxic Effects on Humans</b>	: Skin and Eyes based on data for: (similar material)

## Section 12. Ecological Information

### Ecotoxicity

Ingredient Name or Product name	Species	Period	Result
ARQUAD® 12-50	Fish (LC50)	96 hour(s)	1 to 10 mg/l
	Daphnia (EC50)	48 hour(s)	<1 mg/l
1-dodecanaminium, n,n,n-trimethyl-, chloride	Bluegill. based on data for: (similar material) (LC50)	96 hour(s)	1.94 mg/l
	daphnia based on data for: (similar material) (EC50)	48 hour(s)	0.28 mg/l
Isopropanol	Pimephales promelas (EC50)	48 hour(s)	10000 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	>1400 mg/l
	Pimephales promelas (LC50)	96 hour(s)	6550 mg/l
	Pimephales promelas (LC50)	96 hour(s)	9640 mg/l
	Pimephales promelas (LC50)	96 hour(s)	10400 mg/l
	Pimephales promelas (LC50)	96 hour(s)	11130 mg/l
lauryldimethylamine	Rotofier based on data for: (similar material) (EC50)	48 hour(s)	0.1 mg/l

**Biodegradability and Ecotoxicity Remarks** 60% @ 28 day(s) CBT

**Biodegradable/OECD** Readily biodegradable.

**Products of Degradation** These products are carbon oxides (CO, CO<sub>2</sub>) and water, nitrogen oxides (NO, NO<sub>2</sub>...), halogenated compounds.




## Section 13. Disposal Considerations

**Waste Information** Waste must be disposed of in accordance with federal, state and local environmental control regulations.



**RCRA Classification** **Code:** D001 Ignitable Waste

Consult your local or regional authorities.

## Section 14. Transport Information

Regulatory Information	UN number	Proper shipping name	Class	Packing Group	Label	Additional information
<b>DOT Classification</b>	UN 2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Quaternary ammonium salts)	3 8	II		-
<b>TDG Classification</b>	UN 2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Quaternary ammonium salts)	3 8	II		-
<b>IMDG Class</b>	UN 2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Quaternary ammonium salts)	3	II		-

Continued on Next Page

			8			
<b>IATA-DGR Class</b>	UN 2924	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Quaternary ammonium salts)	3	II		
			8			

## Section 15. Regulatory Information

### HCS Classification

Flammable liquid  
Target organ effects  
Corrosive Material

### U.S. Federal Regulations

TSCA: All intentionally present components are listed on the TSCA inventory.

DSL: All intentionally present components are listed on the DSL.

TSCA 5(a)2 final significant rules: No products were found.

CERCLA: Hazardous substances.: No products were found.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: ARQUAD® 12-50

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: ARQUAD® 12-50: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

SARA 313 Form R Reporting Requirements

Isopropanol

35-45

SARA 313 Supplier Notification

Isopropanol

35-45

### State Regulations

Pennsylvania RTK: Isopropanol: (environmental hazard, generic environmental hazard)

Massachusetts RTK: Isopropanol

New Jersey: Isopropanol

California prop. 65: No products were found.

### WHMIS (Canada)

Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).

Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).

Class E: Corrosive liquid.

CEPA DSL: 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; water; lauryldimethylamine

### European Union

#### Component

1-dodecanaminium, n,n,n-trimethyl-, chloride

#### EC Number

203-927-0

#### EC Status

Not available.

#### EC Annex

Not available.

Isopropanol

200-661-7

Not available.

603-117-00-0

water

231-791-2

Not available.

Not available.

N,N-Dimethyl-1-dodecanamine hydrochloride

Not available.

Not available.

Not available.

lauryldimethylamine

203-943-8

Not available.

Not available.

### Other International Lists

Australia (NICNAS): 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; water; lauryldimethylamine

China: 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; water; lauryldimethylamine

Germany water class: 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; lauryldimethylamine

Japan (MITI): 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; water; lauryldimethylamine

**Continued on Next Page**

Japan (MOL): Isopropanol; lauryldimethylamine

Korea (TCCL): 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; water; lauryldimethylamine

Philippines (RA6969): 1-dodecanaminium, n,n,n-trimethyl-, chloride; Isopropanol; water; lauryldimethylamine

## Section 16. Other Information

### Hazardous Material Information System (U.S.A.)

Health	3
Fire Hazard	3
Reactivity	0
Personal Protection	

### National Fire Protection Association (U.S.A.)



**Other Information** Arquad® is a registered trademark of Akzo Nobel or affiliated companies and is registered in one or more countries including the United States.

**Validation Date** 12/31/2007.

**Previous Validation Date** 5/14/2007.

**Validated by**

Elitania Perez

**Print Date**

12/31/2007.

**Phone Number**

312-544-7038

### Notice to Reader

The information in the material safety data sheet should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable as of the date of publication. However, no warranty is made as to the accuracy of and/or sufficiency of such information and/or suggestions or as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. Buyer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes, including mixing with other products. The information contained herein supersedes all previously issued bulletins on the subject matter covered. If the date on this document is more than three years old, call to make certain that this sheet is current.